

SP-10075/13075BS Electronic Pattern Tacker



Model	SP-10075BS-M	SP-10075BS-ML
Line	Single needle flat seam	Single needle flat seam
Highest sewing speed	2,500 rpm	2,500 rpm
Sewing area	Max.1000×750 mm	Max.1000×750 mm
Thread Wiper	Standard facility	Standard facility
Thread Clamping Device	Variable tension of multi segments	Variable tension of multi segments
Cutting device	Circular Cutting Knife	Circular Cutting Knife
Foot pressure	Auxiliary presser foot + medium presser foot	Auxiliary presser foot + medium presser foot
Press foot height	20mm	20mm
Hook	Heavy material standard hook	Heavy material double shuttle hook

Model	SP-10075BS-HL	SP-13075BS-M
Line	Single needle flat seam	Single needle flat seam
Highest sewing speed	2,500 rpm	2,500 rpm
Sewing area	Max.1000×750 mm	Max.1300×750 mm
Thread Wiper	Standard facility	Standard facility
Thread Clamping Device	Variable tension of multi segments	Variable tension of multi segments
Cutting device	Circular Cutting Knife	Circular Cutting Knife
Foot pressure	Auxiliary presser foot + medium presser foot	Auxiliary presser foot + medium presser foot
Press foot height	20mm	20mm
Hook	Medium-heavy material double shuttle hook	Heavy material standard hook

Model	SP-13075BS-HL	SP-13075BS-ML
Line	Single needle flat seam	Single needle flat seam
Highest sewing speed	2,500 rpm	2,500 rpm
Sewing area	Max.1300×750 mm	Max.1300×750 mm
Thread Wiper	Standard facility	Standard facility
Thread Clamping Device	Variable tension of multi segments	Variable tension of multi segments
Cutting device	Circular Cutting Knife	Circular Cutting Knife
Foot pressure	Auxiliary presser foot + medium presser foot	Auxiliary presser foot + medium presser foot
Press foot height	20mm	20mm
Hook	Heavy material double shuttle hook	Medium-heavy material double shuttle hook