

SP-10075/13075BS Electronic Pattern Tacker



<p>Model Line Highest sewing speed Sewing area Thread Wiper Thread Clamping Device Cutting device Foot pressure Press foot height Hook</p>	<p>SP-10075BS-M Single needle flat seam 2,500 rpm Max.1000×750 mm Standard facility Variable tension of multi segments Circular Cutting Knife Auxiliary presser foot + medium presser foot 20mm Heavy material standard hook</p>	<p>SP-10075BS-ML Single needle flat seam 2,500 rpm Max.1000×750 mm Standard facility Variable tension of multi segments Circular Cutting Knife Auxiliary presser foot + medium presser foot 20mm Heavy material double shuttle hook</p>
---	---	--

<p>Model Line Highest sewing speed Sewing area Thread Wiper Thread Clamping Device Cutting device Foot pressure Press foot height Hook</p>	<p>SP-10075BS-HL Single needle flat seam 2,500 rpm Max.1000×750 mm Standard facility Variable tension of multi segments Circular Cutting Knife Auxiliary presser foot + medium presser foot 20mm Medium-heavy material double shuttle hook</p>	<p>SP-13075BS-M Single needle flat seam 2,500 rpm Max.1300×750 mm Standard facility Variable tension of multi segments Circular Cutting Knife Auxiliary presser foot + medium presser foot 20mm Heavy material standard hook</p>
---	---	---

Model	SP-13075BS-HL	SP-13075BS-ML
Line	Single needle flat seam	Single needle flat seam
Highest sewing speed	2,500 rpm	2,500 rpm
Sewing area	Max.1300×750 mm	Max.1300×750 mm
Thread Wiper	Standard facility	Standard facility
Thread Clamping Device	Variable tension of multi segments	Variable tension of multi segments
Cutting device	Circular Cutting Knife	Circular Cutting Knife
Foot pressure	Auxiliary presser foot + medium presser foot	Auxiliary presser foot + medium presser foot
Press foot height	20mm	20mm
Hook	Heavy material double shuttle hook	Medium-heavy material double shuttle hook