

SP-1010BS Electronic Pattern Sewing Machine



SP-1010BS

 **Suprena**
DESIGN FOR JAPAN

www.suprena-sewing.com

<p style="text-align: center;">Model</p> <p style="text-align: center;">Line</p> <p>Highest sewing speed</p> <p style="text-align: center;">Sewing area</p> <p>Cloth feeding device</p> <p style="text-align: center;">Stitch Length</p> <p>Maximum stitch amount</p> <p>Presser foot drive method</p> <p style="text-align: center;">Press foot height</p> <p>2- step presser foot</p> <p>Rising amount of intermittent foot presser</p> <p>Stroke by intermittent presser foot</p> <p style="text-align: center;">Hook</p> <p style="text-align: center;">Thread Wiper</p> <p>Cutting device</p> <p>Data storage method</p> <p style="text-align: center;">Motor</p> <p>WeightPower</p> <p style="text-align: center;">Air pressure</p>	<p style="text-align: center;">SP-1010BS-H/M/X</p> <p>Single-needle flat seam</p> <p style="text-align: center;">2,700 rpm</p> <p style="text-align: center;">Maximum 100×100 mm</p> <p>Intermittent feeding (driven by pulse motor)</p> <p style="text-align: center;">0.05 - 12.7mm</p> <p style="text-align: center;">20,000 needles/1 pattern</p> <p>S□Pulse motor drive□Pneumatic</p> <p>S□maximum 25 mm ; maximum 30 mm</p> <p style="text-align: center;">All-in-one presser foot</p> <p style="text-align: center;">22 mm</p> <p>0 or 2 - 10 mm□Factory defaults□3mm□</p> <p style="text-align: center;">Double Shuttle Hook</p> <p style="text-align: center;">Standard facility</p> <p style="text-align: center;">Standard facility</p> <p style="text-align: center;">USB or Flash Card</p> <p style="text-align: center;">AC servomotor 550W</p> <p>Head□about 108 kg Operating panel□about 0.6 kg control box□14.2 - 16.2 kg (according to different export countries)</p> <p style="text-align: center;">Single phase 220V□3-phase 380V</p> <p style="text-align: center;">0.5 Mpa 1.8 L/min</p>
<p style="text-align: center;">Model</p> <p style="text-align: center;">Line</p> <p>Highest sewing speed</p> <p style="text-align: center;">Sewing area</p> <p>Cloth feeding device</p> <p style="text-align: center;">Stitch Length</p> <p>Maximum stitch amount</p> <p>Presser foot drive method</p> <p style="text-align: center;">Press foot height</p> <p>2- step presser foot</p> <p>Rising amount of intermittent foot presser</p> <p>Stroke by intermittent presser foot</p> <p style="text-align: center;">Hook</p> <p style="text-align: center;">Thread Wiper</p> <p>Cutting device</p> <p>Data storage method</p> <p style="text-align: center;">Motor</p> <p>WeightPower</p> <p style="text-align: center;">Air pressure</p>	<p style="text-align: center;">SP-1010BS-HS/MS</p> <p>Single-needle flat seam</p> <p style="text-align: center;">2,700 rpm</p> <p style="text-align: center;">Maximum 100×100 mm</p> <p>Intermittent feeding (driven by pulse motor)</p> <p style="text-align: center;">0.05 - 12.7mm</p> <p style="text-align: center;">20,000 needles/1 pattern</p> <p>S□Pulse motor drive □ Pneumatic</p> <p>S□maximum 25 mm ; maximum 30 mm</p> <p style="text-align: center;">All-in-one presser foot</p> <p style="text-align: center;">22 mm</p> <p>0 or 2 - 10 mm□Factory defaults□3mm□</p> <p style="text-align: center;">Double Shuttle Hook</p> <p style="text-align: center;">Standard facility</p> <p style="text-align: center;">Standard facility</p> <p style="text-align: center;">USB or Flash Card</p> <p style="text-align: center;">AC servomotor 550W</p> <p>Head□about 108 kg Operating panel□about 0.6 kg control box□14.2 - 16.2 kg (according to different export countries)</p> <p style="text-align: center;">Single phase 220V, 3-phase 380V</p> <p style="text-align: center;">0.5 Mpa 1.8 L/min</p>