

SP-1310/2210AS Electronic Pattern Sewing Machine



SP-1310/2210AS

 **Suprena**
DESIGN FOR JAPAN

www.suprena-sewing.com

	SP-1310AS-HS/MS	SP-1310AS-H/M/X
Model	Sing-needle flat seam	Sing-needle flat seam
Line	2700rpm	2,700rpm
Highest sewing speed	Max.130×100mm	Max.130×100mm
Sewing area	Intermittent feeding(Pulse motor drive mode)	Intermittent feeding(Pulse motor drive mode)
Cloth feeding mode	0.05-12.7mm	0.05-12.7mm
Stitch Length	20,000 needles/1 pattern	20,000 needles/1 pattern
Maximum stitch amount	Integrated presser foot□ Divided presser foot	Integrated presser foot□ Divided presser foot
2- step presser foot	500000 stitch can be stored in build-inmemory	500000 stitch can be stored in build-inmemory
Storage amount of stitches	22mm	22mm
Rising amount of intermittent foot presser	0 or 2-10mm□Factory defaults□3mm□	0 or 2-10mm□Factory defaults□3mm□
Stroke by intermittent presser foot	Standard facility	Standard facility
Thread Wiper	Standard facility	Standard facility
Cutting device	50	50
Customer program amount	9	9
Recycle programme No.	AC servomotor 550W	AC servomotor 550W
Motor	carton□Head Control box□about 104kg□Control	carton□Head Control box□about 104kg□Control
Weight	box□20kg□table&stand□30kg□wooden case□about 160kg	box□20kg□table&stand□30kg□wooden case□about 160kg
Power	Single phase 100~120V□200~240V□3-phase	Single phase 100~120V□200~240V□3-phase
Air pressure	200~240V□380~415V□350V 0.5Mpa□1.8L/min	200~240V□380~415V□350V 0.5Mpa□1.8L/min