

SP-1310AS-H/CH Sliding Pattern Tacker Machine



SP-1310AS-H

 **Suprena**
DESIGN FOR JAPAN

www.suprena-sewing.com

| | |
|--|---|
| Model | SP-1310AS-H/CH |
| Line | Sing-needle flat seam |
| Highest sewing speed | 2,700 rpm |
| Sewing area | Max.130×100mm |
| Cloth feeding device | Intermittent feeding(Servo motor drive mode) |
| Stitch Length | 0.05-12.7mm |
| Maximum stitch amount | 20,000 needles/1 pattern |
| Storage amount of stitches | 500000 stitch can be stored |
| 2- step presser foot | Integrated presser foot□ Divided presser foot |
| Rising amount of intermittent foot presser | 22mm |
| Stroke by intermittent presser foot | 0 or 2-10mm□Factory defaults□3mm□ |
| Thread Wiper | Standard facility |
| Cutting device | Standard facility |
| Customer program amount | 50 |
| Recycle programme No. | 9 |
| Motor | AC servomotor 550W |
| Weight | carton□Head Control box□about 104kg□Control box□20kg |
| Power | table&stand□30kg□wooden case□about 160kg |
| Air pressure | Single phase 100~120V□200~240V□3-phase 200~240V□380~415V□350V |
| | 0.5Mpa□1.8L/min |