

SP-1510BS Electronic Pattern Sewing Machine



SP-1510BS

 **Suprena**
DESIGN FOR JAPAN

www.suprena-sewing.com

<p>Model Line Highest sewing speed Sewing area Cloth feeding device Stitch Length Maximum stitch amount Presser foot drive method Press foot height 2- step presser foot Rising amount of intermittent foot presser Stroke by intermittent presser foot Hook Thread Wiper Cutting device Data storage method Weight Power Air pressure Motor</p>	<p>SP-1510BS-HS/MS Single-needle flat seam 2,700 rpm Maximum 150×100mm Intermittent feeding (driven by pulse motor) 0.05 - 12.7mm 20,000 needles/1 pattern S□Pulse motor drive□Pneumatic S□maximum 25 mm ; maximum 30 mm All-in-one presser foot 22 mm 0 or 2 - 10 mm□Factory defaults□3mm□ Double Shuttle Hook Standard facility Standard facility USB or Flash Card Head□about 108 kg Operating panel□about 0.6 kg control box□14.2 - 16.2 kg (according to different export countries) Single phase 220V□3-phase 380V 0.5 Mpa 1.8 L/min AC servomotor 550W</p>
---	--

<p>Model Line Highest sewing speed Sewing area Cloth feeding device Stitch Length Maximum stitch amount Presser foot drive method Press foot height 2- step presser foot Rising amount of intermittent foot presser Stroke by intermittent presser foot Hook Thread Wiper Cutting device Data storage method Weight Power Air pressure Motor</p>	<p>SP-1510BS-H/M/X Single-needle flat seam 2,700 rpm Maximum 150×100mm Intermittent feeding (driven by pulse motor) 0.05 - 12.7mm 20,000 needles/1 pattern S□Pulse motor drive□Pneumatic S□maximum 25 mm ; maximum 30 mm All-in-one presser foot 22 mm 0 or 2 - 10 mm□Factory defaults□3mm□ Double Shuttle Hook Standard facility Standard facility USB or Flash Card Head□about 108 kg Operating panel□about 0.6 kg control box□14.2 - 16.2 kg (according to different export countries) Single phase 220V□3-phase 380V 0.5 Mpa 1.8 L/min AC servomotor 550W</p>
---	--

