

SP-2210BS/3020BS-XZ Small Mouth Pattern Sewing Machine



SP-2210BS/3020BS-XZ

Suprena
DESIGN FOR JAPAN

www.suprena-sewing.com

Model	SP-2210BS-XZ
Line	Sing-needle flat seam
Highest sewing speed	2,700 rpm
Sewing area	Max.220×100 mm
Cloth feeding device	Intermittent feeding(Pulse motor drive mode)
Stitch Length	0.05 - 12.7mm
Maximum stitch amount	20,000 needles/1 pattern
Presser foot drive method	Pneumatic
Press foot height	Max. 30mm
2- step presser foot	Divided presser foot
Rising amount of intermittent foot presser	22 mm
Stroke by intermittent presser foot	0 or 2-10mm□Factory defaults□3mm□
Hook	Double Shuttle Hook
Thread Wiper	Standard facility
Cutting device	Standard facility
Tension device	Elctric tension device
Data storage method	USB or Flash memory (You can sew pattern with CF card)
Motor	AC servomotor 550W
WeightPower	Head□about 108 kg Operating panel□about 0.6 kg control box
Air pressure	14.2 - 16.2 kg (according to different export countries) Single phase 220V Three-phase 380V 0.5 Mpa 1.8 L/min

Model	SP-3020BS-XZ
Line	Sing-needle flat seam
Highest sewing speed	2,700 rpm
Sewing area	Max.300×200 mm
Cloth feeding device	Intermittent feeding(Pulse motor drive mode)
Stitch Length	0.05 - 12.7mm
Maximum stitch amount	20,000 needles/1 pattern
Presser foot drive method	Pneumatic
Press foot height	Max. 30mm
2- step presser foot	Divided presser foot
Rising amount of intermittent foot	22 mm
presser	0 or 2-10mm□Factory defaults□3mm□
Stroke by intermittent presser foot	Double Shuttle Hook
Hook	Standard facility
Thread Wiper	Standard facility
Cutting device	Elctric tension device
Tension device	USB or Flash memory (You can sew pattern with
Data storage method	CF card)
Motor	AC servomotor 550W
WeightPower	Head□about 108 kg Operating panel□about 0.6 kg
Air pressure	control box□14.2 - 16.2 kg (according to different
	export countries)
	Single phase 220V Three-phase 380V
	0.5 Mpa 1.8 L/min