

SP-2210BS/3020BS-XZ Small Mouth Pattern Sewing Machine



SP-2210BS/3020BS-XZ

 **Suprena**
DESIGN FOR JAPAN

www.suprena-sewing.com

<p style="text-align: center;">Model</p> <p style="text-align: center;">Line</p> <p>Highest sewing speed</p> <p style="text-align: center;">Sewing area</p> <p style="text-align: center;">Cloth feeding device</p> <p style="text-align: center;">Stitch Length</p> <p style="text-align: center;">Maximum stitch amount</p> <p style="text-align: center;">Presser foot drive method</p> <p style="text-align: center;">Press foot height</p> <p style="text-align: center;">2- step presser foot</p> <p>Rising amount of intermittent foot presser</p> <p>Stroke by intermittent presser foot Hook</p> <p style="text-align: center;">Thread Wiper</p> <p style="text-align: center;">Cutting device</p> <p style="text-align: center;">Tension device</p> <p style="text-align: center;">Data storage method</p> <p style="text-align: center;">Motor</p> <p style="text-align: center;">WeightPower</p> <p style="text-align: center;">Air pressure</p>	<p style="text-align: center;">SP-2210BS-XZ</p> <p>Sing-needle flat seam</p> <p style="text-align: center;">2,700 rpm</p> <p style="text-align: center;">Max.220×100 mm</p> <p>Intermittent feeding(Pulse motor drive mode)</p> <p style="text-align: center;">0.05 - 12.7mm</p> <p style="text-align: center;">20,000 needles/1 pattern</p> <p style="text-align: center;">Pneumatic</p> <p style="text-align: center;">Max. 30mm</p> <p style="text-align: center;">Divided presser foot</p> <p style="text-align: center;">22 mm</p> <p style="text-align: center;">0 or 2-10mm□Factory defaults□3mm□</p> <p style="text-align: center;">Double Shuttle Hook</p> <p style="text-align: center;">Standard facility</p> <p style="text-align: center;">Standard facility</p> <p style="text-align: center;">Elctric tension device</p> <p>USB or Flash memory (You can sew pattern with CF card)</p> <p style="text-align: center;">AC servomotor 550W</p> <p>Head□about 108 kg Operating panel□about 0.6 kg control box</p> <p style="text-align: center;">14.2 - 16.2 kg (according to different export countries)</p> <p style="text-align: center;">Single phase 220V Three-phase 380V</p> <p style="text-align: center;">0.5 Mpa 1.8 L/min</p>
---	---

<p style="text-align: center;">Model</p> <p style="text-align: center;">Line</p> <p>Highest sewing speed</p> <p style="text-align: center;">Sewing area</p> <p style="text-align: center;">Cloth feeding device</p> <p style="text-align: center;">Stitch Length</p> <p style="text-align: center;">Maximum stitch amount</p> <p style="text-align: center;">Presser foot drive method</p> <p style="text-align: center;">Press foot height</p> <p style="text-align: center;">2- step presser foot</p> <p>Rising amount of intermittent foot presser</p> <p>Stroke by intermittent presser foot Hook</p> <p style="text-align: center;">Thread Wiper</p> <p style="text-align: center;">Cutting device</p> <p style="text-align: center;">Tension device</p> <p style="text-align: center;">Data storage method</p> <p style="text-align: center;">Motor</p> <p style="text-align: center;">WeightPower</p> <p style="text-align: center;">Air pressure</p>	<p style="text-align: center;">SP-3020BS-XZ</p> <p>Sing-needle flat seam</p> <p style="text-align: center;">2,700 rpm</p> <p style="text-align: center;">Max.300×200 mm</p> <p>Intermittent feeding(Pulse motor drive mode)</p> <p style="text-align: center;">0.05 - 12.7mm</p> <p style="text-align: center;">20,000 needles/1 pattern</p> <p style="text-align: center;">Pneumatic</p> <p style="text-align: center;">Max. 30mm</p> <p style="text-align: center;">Divided presser foot</p> <p style="text-align: center;">22 mm</p> <p style="text-align: center;">0 or 2-10mm□Factory defaults□3mm□</p> <p style="text-align: center;">Double Shuttle Hook</p> <p style="text-align: center;">Standard facility</p> <p style="text-align: center;">Standard facility</p> <p style="text-align: center;">Elctric tension device</p> <p>USB or Flash memory (You can sew pattern with CF card)</p> <p style="text-align: center;">AC servomotor 550W</p> <p>Head□about 108 kg Operating panel□about 0.6 kg control box□14.2 - 16.2 kg (according to different export countries)</p> <p style="text-align: center;">Single phase 220V Three-phase 380V</p> <p style="text-align: center;">0.5 Mpa 1.8 L/min</p>
---	--