

# SP-3020AS Electronic Pattern Sewing Machine



SP-3020AS

 **Suprena**  
DESIGN FOR JAPAN

[www.suprena-sewing.com](http://www.suprena-sewing.com)

<b>Model</b>	<b>SP-3020AS-H</b>
<b>Line</b>	<b>Sing-needle flat seam</b>
<b>Highest sewing speed</b>	<b>2,700 rpm</b>
<b>Sewing area</b>	<b>Max.300×200mm</b>
<b>Cloth feeding mode</b>	<b>Intermittent feeding(Servo motor drive mode)</b>
<b>Stitch Length</b>	<b>0.05-12.7mm</b>
<b>Maximum stitch amount</b>	<b>20,000 needles/1 pattern</b>
<b>Storage amount of stitches</b>	<b>500000 stitch can be stored</b>
<b>Presser foot drive method</b>	<b>Pneumatic</b>
<b>Press foot height</b>	<b>Max. 30mm</b>
<b>2- step presser foot</b>	<b>All-in-one presser foot</b>
<b>Big foot presser height</b>	<b>Max. 30mm</b>
<b>Big foot presser method</b>	<b>All-in-one presser foot</b>
<b>Rising amount of intermittent foot presser</b>	<b>22mm</b>
<b>Stroke by intermittent presser foot</b>	<b>0 or 2-10mm□Factory defaults□3mm□ Standard facility</b>
<b>Thread Wiper</b>	<b>Standard facility</b>
<b>Cutting device</b>	<b>50</b>
<b>Customer program amount</b>	<b>9</b>
<b>Recycle programme No.</b>	<b>AC servomotor 550W</b>
<b>Motor</b>	<b>Head□About 150kg</b>
<b>Weight</b>	<b>Single phase100~120V□200~240V</b>
<b>Power</b>	<b>3-</b>
<b>Air pressure</b>	<b>phase200~240V□380~415V□350V</b>
	<b>0.5Mpa□1.8L/min</b>

<b>Model</b>	<b>SP-3020AS-M</b>
<b>Line</b>	<b>Sing-needle flat seam</b>
<b>Highest sewing speed</b>	<b>2,700 rpm</b>
<b>Sewing area</b>	<b>Max.300×200mm</b>
<b>Cloth feeding mode</b>	<b>Intermittent feeding(Servo motor drive mode)</b>
<b>Stitch Length</b>	<b>0.05-12.7mm</b>
<b>Maximum stitch amount</b>	<b>20,000 needles/1 pattern</b>
<b>Storage amount of stitches</b>	<b>500000 stitch can be stored</b>
<b>Presser foot drive method</b>	<b>Pneumatic</b>
<b>Press foot height</b>	<b>Max. 30mm</b>
<b>2- step presser foot</b>	<b>All-in-one presser foot</b>
<b>Big foot presser height</b>	<b>Max. 30mm</b>
<b>Big foot presser method</b>	<b>All-in-one presser foot</b>
<b>Rising amount of intermittent foot presser</b>	<b>22mm</b>
<b>Stroke by intermittent presser foot</b>	<b>0 or 2-10mm□Factory defaults□3mm□</b>
<b>Thread Wiper</b>	<b>Standard facility</b>
<b>Cutting device</b>	<b>Standard facility</b>
<b>Customer program amount</b>	<b>50</b>
<b>Recyle programme No.</b>	<b>9</b>
<b>Motor</b>	<b>AC servomotor 550W</b>
<b>Weight</b>	<b>Head□About 150kg</b>
<b>Power</b>	<b>Single phase100~120V□200~240V</b>
<b>Air pressure</b>	<b>3- phase200~240V□380~415V□350V</b>
	<b>0.5Mpa□1.8L/min</b>

<b>Model</b>	<b>SP-3020AS-X</b>
<b>Line</b>	<b>Sing-needle flat seam</b>
<b>Highest sewing speed</b>	<b>2,700 rpm</b>
<b>Sewing area</b>	<b>Max.300×200mm</b>
<b>Cloth feeding mode</b>	<b>Intermittent feeding(Servo motor drive mode)</b>
<b>Stitch Length</b>	<b>0.05-12.7mm</b>
<b>Maximum stitch amount</b>	<b>20,000 needles/1 pattern</b>
<b>Storage amount of stitches</b>	<b>500000 stitch can be stored</b>
<b>Presser foot drive method</b>	<b>Pneumatic</b>
<b>Press foot height</b>	<b>Max. 30mm</b>
<b>2- step presser foot</b>	<b>All-in-one presser foot</b>
<b>Big foot presser height</b>	<b>Max. 30mm</b>
<b>Big foot presser method</b>	<b>All-in-one presser foot</b>
<b>Rising amount of intermittent foot presser</b>	<b>22mm</b>
<b>Stroke by intermittent presser foot</b>	<b>0 or 2-10mm□Factory defaults□3mm□</b>
<b>Thread Wiper</b>	<b>Standard facility</b>
<b>Cutting device</b>	<b>Standard facility</b>
<b>Customer program amount</b>	<b>50</b>
<b>Recycle programme No.</b>	<b>9</b>
<b>Motor</b>	<b>AC servomotor 550W</b>
<b>Weight</b>	<b>Head□About 150kg</b>
<b>Power</b>	<b>Single phase100~120V□200~240V</b>
<b>Air pressure</b>	<b>3-phase200~240V□380~415V□350V</b>
	<b>0.5Mpa□1.8L/min</b>