

SP-3020ASF-H/M Electronic Pattern Sewing Machine



SP-3020ASF-H/M

 **Suprena**
DESIGN FOR JAPAN

www.suprena-sewing.com

Model	SP-3020ASF-H	SP-3020ASF-M
Line	Sing-needle flat seam	Sing-needle flat seam
Highest sewing speed	2,700 rpm	2,700 rpm
Sewing area	Max.300×200mm	Max.300×200mm
Cloth feeding mode	Intermittent feeding□Pulse motor drive mode□	Intermittent feeding□Pulse motor drive mode□
Stitch Length	0.05-12.7mm	0.05-12.7mm
Maximum stitch amount	20,000 needles/1 pattern	20,000 needles/1 pattern
Storage amount of stitches	500000 stitch can be stored in build-	500000 stitch can be stored in build-inmomery
Presser foot drive method	inmomery	Pneumatic
Press foot height	Pneumatic	Max. 30mm
2- step presser foot	Max. 30mm	All-in-one presser foot
Big foot presser height	All-in-one presser foot	Max. 30mm
Big foot presser method	Max. 30mm	All-in-one presser foot
Rising amount of intermittent	All-in-one presser foot	22mm
foot presser	22mm	0 or 2-10mm□Factory defaults□3mm□
Stroke by intermittent presser	0 or 2-10mm□Factory defaults□3mm□	Standard facility
foot	Standard facility	Standard facility
Thread Wiper	Standard facility	50
Cutting device	50	9
Customer program amount	9	AC servomotor 550W
Recycle programme No.	AC servomotor 550W	Head□About 150kg
Motor	Head□About 150kg	Single phase100~120V□200~240V□3-phase
Weight	Single phase100~120V□200~240V	200~240V□380~415V□350V
PowerAir pressure	3-phase 200~240V□380~415V□350V	0.5Mpa□1.8L/min
	0.5Mpa□1.8L/min	