

SP-3020BS Electronic Pattern Sewing Machine



SP-3020BS

 **Suprena**
DESIGN FOR JAPAN

www.suprena-sewing.com

Model	SP-3020BS-H/M/X
Line	Sing-needle flat seam
Highest sewing speed	2,700 rpm
Sewing area	Max.300×200 mm
Cloth feeding device	Intermittent feeding(Pulse motor drive mode)
Stitch Length	0.05 - 12.7mm
Maximum stitch amount	20,000 needles/1 pattern
Presser foot drive method	Pneumatic
Press foot height	Max. 30mm
2- step presser foot	All-in-one presser foot
Rising amount of intermittent	22 mm
foot presser	0 or 2-10mm□Factory defaults□3mm□
Stroke by intermittent	Double Shuttle Hook
presser foot	Standard facility
Hook	Standard facility
Thread Wiper	Elctric tension device
Cutting device	USB or Flash memory (You can sew pattern with
Tension device	CF card)
Data storage method	AC servomotor 550W
Motor	Head□about 135 kg, Operating panel□about 0.6 kg
WeightPower	control box□14.2 - 16.2 kg (according to different
Air pressure	export countries)
	Single phase 220V Three-phase 380V
	0.5 Mpa 1.8 L/min