

# SP-3020R Electronic Pattern Sewing Machine



**SP-3020BS**

**Suprena**  
DESIGN FOR JAPAN

[www.suprena-sewing.com](http://www.suprena-sewing.com)

<b>Model</b>	<b>SP-3020R-H/M</b>
Line	Sing-needle flat seam
Highest sewing speed	2,700 rpm
Sewing area	Max.300×200 mm
Cloth feeding device	Intermittent feeding(Servo motor drive mode)
Stitch Length	0.05 - 12.7mm
Maximum stitch amount	20,000 needles/1 pattern
Presser foot drive method	Pneumatic
Press foot height	Max. 30mm
2- step presser foot	All-in-one presser foot
Rising amount of intermittent foot presser	22 mm
Stroke by intermittent presser foot	0 or 2-10mm□Factory defaults□3mm□
Hook	Two times of shuttle hooks
Thread Wiper	Standard facility
Cutting device	Standard facility
Tension device	Elctric tension device
Data storage method	USB or Flash memory (You can sew pattern with CF card)
Motor	AC servomotor 550W
Weight	Head□about 135 kg, Operating panel□about 0.6 kg control box□14.2 - 16.2 kg (according to differentexport countries)
Power	Single phase 220V Three-phase 380V
Air pressure	0.5 Mpa 1.8 L/min