

SP-6030/6040AP Electronic Pattern Sewing Machine



SP-6030/6040AP

 **Suprena**
DESIGN FOR JAPAN

www.suprena-sewing.com

Model	SP-6030AP-H/M/X	SP-6040AP-H/M/X
Line	Sing-needle flat seam	Sing-needle flat seam
Highest sewing speed	2,700 rpm	2,700 rpm
Sewing area	Max. 600×300mm	Max. 600×300mm
Cloth feeding mode	Intermittent feeding(Servo motor drive mode)	Intermittent feeding(Servo motor drive mode)
Stitch Length	0.05-12.7mm	0.05-12.7mm
Maximum stitch amount	20,000 needles/1 pattern	20,000 needles/1 pattern
Storage amount of stitches	500000 stitch can be stored	500000 stitch can be stored
Presser foot drive method	Pneumatic	Pneumatic
Press foot height	Max. 30mm	Max. 30mm
2- step presser foot	All-in-one presser foot	All-in-one presser foot
Big foot presser height	Max. 30mm	Max. 30mm
Big foot presser method	All-in-one presser foot	All-in-one presser foot
Rising amount of intermittent foot presser	22mm	22mm
Stroke by intermittent presser foot	0 or 2-10mm□Factory defaults□3mm□	0 or 2-10mm□Factory defaults□3mm□
Thread Wiper	Standard facility	Standard facility
Cutting device	Standard facility	Standard facility
Customer program amount	50	50
Recycle programme No.	9	9
Motor	AC servomotor 550W	AC servomotor 550W
Weight	Head□About 150kg	Head□About 150kg
Power	Single phase200~240V	Single phase200~240V
Air pressure	0.5Mpa□1.8L/min	0.5Mpa□1.8L/min